



# Motorola Satellite Series<sup>™</sup> 9520 Mobile Telephone

This full-featured, permanently installed mobile telephone is designed for in-vehicle operation with the Iridium® network.

Hands-free functionality and external antenna options complete the package.





### Satellite Series<sup>™</sup> 9520 Mobile Phone

### Visual/Audible Features

- Graphic LCD Display (4 x 6 characters)
- 32-Digit Number Capacity (max. number of digits)
- 16-Digit Name Tag (maximum character length)
- Illuminated Keypad and Display
- Visual Display of Volume Level Settings
- Status Review of Features
- Automatic Language Selections Based on SIM Card
- Multiple Language Choices for Prompts
- 10 Dedicated Control Keys

#### Call Related Features

- Selectable Ringer Tone-10 choices
- Selectable Keypad Tone-3 choices
- Volume Adjustment (earpiece or ringer)
- Auto Redial (when system busy)
- Clear Last Digit/Clear All Digits
- International Access Key Sequence (+key)
- Master Clear
- Master Reset
- Fixed Dialing
- Quick Access Interface (user configurable)
- Unanswered call indicator

### Memory

- Phone–Numbered Memory (100 Locations)
- SIM Card 155 Memory Locations
- Alpha Name Storage (recall by name or location)
- Last 10 Numbers Dialed
- One-Touch Dialing
- Memory Scroll By Location Number

## Usage Control ■ Electronic Lock

- Automatic Lock
- Display/Change Unlock Code
- Display Call Timers: Last Call/Total
- Programmable Audible Call Timer:
  - One Time
  - Repeatable (user definable)
- Automatic Display Call Timer (while in a call)
- Call Restriction Levels:
  - · Restrict Keypad Dialing
  - Incoming Calls
  - Number Length

## Mobile Application Features ■ Integrated SIM Card Reader in Hang-up Cup

- Entertainment Mute (dependent on vehicle's AM/FM radio system)\*\*
- Automatic Answer
- Automatic Handsfree
- Safety Timer

Full ( and FCC compliance.

### Basic Telephony

Basic Telephony (bi-directional access to PSTN and other IRIDIUM system subscriber units.)

### Tel ephony Suppl ementary Services

- Call Barring
- Call Forwarding Unconditional
- Call Forwarding on Mobile Subscriber Busy (via the menu)
- Call Forwarding on Subscriber Not Reachable
- Personal Mailbox with Numeric Messaging, Text Messaging and Voicemail

#### Data Services

Data Capable

### System Services

- DTMF Tones
- Pending Call Drop Notification
- Subscriber Identity Authentication

### PRODUCT SPECIFICATIONS

TRODUCT SIL	-CILICATIONS
Transceiver Dimensions:	24.69L x 8.61W X 3.99D (cm)
	9.72L x 3.39W x 1.57D (in)
Transceiver Weight:	595g (1.3lbs.)
SIM Card Slot:	ID-1 Credit Card Size (in hang-up cup)
Operating Frequency:	1616–1626.5 MHz
Operating Temperature:	-30/+60 degrees Celsius
Duplexing Method:	Time Division Duplex (TDD)
Multiplexing Method:	TDMA/FDMA
Link Margin: (with exterior antenna)	12.5 dB average
Power:	0.57 Watts average + +
Sensitivity:	-117.9 dBm++
TX Spurs General EIRP:	-71 dBc++
TX Spurs GNSS 1559-1605 MHz EIRP:	-91 dBc++
TX Noise GNSS 1559-1605 MHz EIRP:	-81 dBc/MHz++
Antenna Options:	Mobile Magnetic Mount Antenna Mobile Permanent Mount Antenna Fixed Mast Antenna

Product appearance & specifications subject to change without notice.

, MOTOROLA, OPTIMAX and SATELLITE SERIES logo are trademarks of Motorola

©2001 Iridium and the Iridium logo are registered trademarks and service marks of Iridium Satellite LLC.

Iridium Satellite LLC 8440 South River Parkway Tempe, AZ 85284 USA

Toll Free: 1-866-947-4348 T: 1-480-752-5155 F: 1-480-752-1105 www.iridium.com

